



**CERTIFICATO DI OMOLOGAZIONE DI TIPO**  
*TYPE APPROVAL CERTIFICATE*  
**N. DIP082018XT/002**

Si certifica che il seguente prodotto soddisfa le prescrizioni delle norme RINA per l'omologazione di tipo.  
*This is to certify that the product identified below is in compliance with the applicable requirements of the RINA type approval system.*

<b>Descrizione</b> <i>Description</i>	<b>Porta stagna</b> <i>Watertight door</i>
<b>Tipo</b> <i>Type</i>	<b>Watertight Flush Steel Door</b>
<b>Fabbricante</b>	<b>BOFOR DENIZCILIK SANAYI VE TICARET LTD.STI.</b>
<b>Luogo di produzione</b> <i>Manufacturer</i>	<b>IMES SANAYI SITESI, C BLOK, 308 SOKAK, NO.18 Y.DUDULLU,</b>
<i>Place of manufacture</i>	<b>UMRANIYE, ISTANBUL</b>
<b>Norme di riferimento</b> <i>Reference standards</i>	<b>RINA Rules</b> <i>RINA Rules</i>



Rilasciato a **ISTANBUL** il **15 Ottobre 2019**.  
Questo Certificato è valido fino al **15 Ottobre 2022**  
*Issued in ISTANBUL on October 15, 2019 . This Certificate is valid until October 15, 2022*

Questo Certificato e' composto di 1 pagina e di 1 allegato  
*This certificate consists of this page and 1 enclosure*

RINA Services S.p.A.

**Cem Cakmak**







**CERTIFICATO DI OMOLOGAZIONE DI TIPO**

*TYPE APPROVAL CERTIFICATE*

**DIP082018XT/002**

**Allegato - Pagina 1/1**

*Enclosure - Page 1 of 1*

**STEEL DOOR**

*Reference documents:*

- Job nr. 2019/XT/01/273
- Job nr. 2008/XT/01/708
- Job nr. 2015/XT/01/477

*Product Description:*

- Watertight doors: 590 x 590 mm; 590 mm x 1460 mm; 1072 mm x 2072 mm.
- See drawings approved on 30 March 2009 with nr. DIP-43017 and 15 September 2015 with nr. ISDP-17246 and 15 October 2019 with nr. ISDP-23907.
- If the same construction materials, as per approved a.m. drawing, will be used, the T.A. may be considered suitable for all the dimensions so that: short side between 590 and 1072 mm and long side between 590 and 2072 mm.
- Doors suitable for an hydraulic pressure of 5.0 m head.
- Doors fitted on escape ways are to be operable by both sides (handles are to be permanently fixed).
- When located in houseside, the doors are to be hinged at the forward edge.
- After installation on board, a water jet test is to be carried out.
- The T.A. is relevant only to "watertightness".

*Fields of application:*

- Watertight door

**10/15/2019**

***Istanbul January 7th, 2019***

