



TYPE APPROVAL CERTIFICATE
TYPE APPROVAL CERTIFICATE
N. DIP104118XT

This is to certify that the product identified below is in compliance with the applicable requirements of the RINA type approval system.

This is to certify that the product identified below is in compliance with the applicable requirements of the RINA type approval system.

Descrizione <i>Description</i>	Boccaportelli stagni Watertight Aluminium Casting Alloy Flush Hatch <i>Watertight hatches (Aluminium)</i>
Tipo <i>Type</i>	500 x 500 mm - 600 x 600 mm
Fabbricante <i>Manufacturer</i>	BOFOR DENIZCILIK SANAYI VE TICARET LTD.STI.
Luogo di produzione <i>Place of manufacture</i>	IMES SANAYI SITESI, C BLOK, 308 SOKAK, NO.18 Y.DUDULLU, UMRANIYE, ISTANBUL TURKEY
Norme di riferimento <i>Reference standards</i>	Rules for the Classification of Yachts designed for Commercial Use, Rules for the Classification of Pleasure Yachts <i>Rules for the Classification of Yachts designed for Commercial Use, Rules for the Classification of Pleasure Yachts</i>



Rilasciato a **ISTANBUL** l' **8 Marzo 2019**. Questo
Certificato è valido fino al **8 Marzo 2022**
*Issued in ISTANBUL on March 8, 2019 . This Certificate is
valid until March 8, 2022*

Questo Certificato e' composto di 1 pagina e di 1 allegato
This certificate consists of this page and 1 enclosure



RINA Services S.p.A.
Cem Cakmak





TYPE APPROVAL CERTIFICATE

TYPE APPROVAL CERTIFICATE

DIP104118XT

Allegato - Pagina 1/1

Enclosure - Page 1 of 1

500 x 500 mm - 600 x 600 mm

Reference documents:

- Job nr. 2018/XT/01/995

Product Description:

- Watertight hatches: 500 x 500 mm; 600 x 600 mm

- See drawings approved with nr. from ISDP-22525.

- If the same construction materials, as per approved a.m. drawings, will be used, the T.A. may be considered suitable for all the dimensions so that: short side between 500 and 600 mm and long side between 500 and 600 mm.

- The hatches are to be hinged at the forward edge.

- After installation on board, a water jet test is to be carried out.

- The T.A. is relevant only to "watertightness".

- Hatches suitable for an hydraulic pressure of 3.0 m head.

- Hatches fitted on escape ways are to be operable by both sides (handles are to be permanently fixed).

- Hatches suitable for yachts designed for Commercial use having $GT < 500$ and fitted other than the engine room and galley boundaries.

- Hatches suitable for pleasure yachts having any GT and fitted other than the engine room and galley boundaries.

- Hatches suitable for pleasure yachts having $GT \leq 300$.

Fields of application:

- Watertight hatches for "RINA Rules for the Classification of Yachts designed for Commercial Use" and "RINA Rules for the Classification of Pleasure Yachts".

08.03.2019

İstanbul, March 8th, 2019

