



TYPE APPROVAL CERTIFICATE

TYPE APPROVAL CERTIFICATE

N. DIP017018XT

This is to certify that the product identified below is in compliance with the applicable requirements of the RINA type approval system.

This is to certify that the product identified below is in compliance with the applicable requirements of the RINA type approval system.

| | |
|---|--|
| Descrizione <i>Description</i> | Boccaportelli stagni(Acciaio) <i>Watertight hatches (Steel)</i> |
| Tipo <i>Type</i> | 650 x 650 mm - 900 x 900 mm - 1000 x 1200 mm |
| Fabbricante <i>Manufacturer</i> | BOFOR DENIZCILIK SANAYI VE TICARET LTD.STI. |
| Luogo di produzione <i>Place of manufacture</i> | IMES SANAYI SITESI, C BLOK, 308 SOKAK, NO.18 Y.DUDULLU, UMRANIYE, ISTANBUL TURKEY |
| Norme di riferimento <i>Reference standards</i> | Rules for the Classification of Yachts designed for Commercial Use, Rules for the Classification of Pleasure Yachts Rules for the Classification of Yachts designed for Commercial Use, Rules for the Classification of Pleasure Yachts |



RINA Cem Cakmak
Head of Turkey Yachting Centre
RINA Istanbul
563

Rilasciato a **ISTANBUL** il **24 Maggio 2018**.

Questo Certificato è valido fino al **24 Maggio 2021**

Issued in ISTANBUL on May 24, 2018 . This Certificate is valid until May 24, 2021

RINA Services S.p.A.

Questo Certificato e' composto di 1 pagina e di 1 allegato

This certificate consists of this page and 1 enclosure





TYPE APPROVAL CERTIFICATE

TYPE APPROVAL CERTIFICATE

DIP017018XT

Allegato - Pagina 1/1

Enclosure - Page 1 of 1

650 x 650 mm - 900 x 900 mm - 1000 x 1200 mm

Reference documents:

- Job nr. 2018/XT/01/170

Product Description:

- *Watertight hatches:*

650 x 650 mm with 4 dogs with 2 hinges

650 x 650 mm - 900 x 900 mm with 6 dogs with 2 hinges

900 x 900 mm - 1000 x 1200 mm with 8 dogs with 2 hinges

- See drawings approved with nr. from ISDP-21373 , ISDP-21374 , ISDP-21485

- If the same construction materials, as per approved a.m. drawings, will be used, the T.A. may be considered suitable for all the dimensions so that: short side between 650 and 1000 mm and long side between 650 and 1200 mm.

- The hatches are to be hinged at the forward edge.

- After installation on board, a water jet test is to be carried out.

- The T.A. is relevant only to "watertightness".

- Hatches suitable for an hydraulic pressure of 2.0 m head.

- Hatches fitted on escape ways are to be operable by both sides (handles are to be permanently fixed).

- Hatches suitable for yachts designed for Commercial use having GT < 500 and fitted other than the engine room and galley boundaries.

- Hatches suitable for pleasure yachts having any GT and fitted other than the engine room and galley boundaries.

- Hatches suitable for pleasure yachts having GT <= 300.

Fields of application:

- Watertight hatches for "RINA Rules for the Classification of Yachts designed for Commercial Use" and "RINA Rules for the Classification of Pleasure Yachts".

Istanbul, May 24th, 2018

